

## ARMSTRONG METALWORKS™ MESH

- Mesh Metal provides a contemporary design aesthetic to achieve an industrial and contemporary look
- 8 design options
- Installed on standard Peakform Prelude 24mm suspension systems
- Ideal choice for transport hubs, renovation projects or large circulation area
- 100% upward demountable
- Configurable option (dimension, edge) available for expanded mesh pattern

Panel Options	Mesh: Profile for Exposed Structures				
<b>Edge details</b>	<p>Board 24 mm Exposed Grid</p>				
<b>Material</b>	Galvanized Steel				
<b>Patterns</b>	<b>Expanded Mesh</b>				
<b>Weight</b>	<table border="0"> <tr> <td> <p><b>Hexagon 1</b> 7.2mm x 26.4mm 74% Open Area 5.0kg/m<sup>2</sup></p> </td> <td> <p><b>Hexagon 3</b> 3.75mm x 26.4mm 80% Open Area 7.1kg/m<sup>2</sup></p> </td> <td> <p><b>Rhombic 4</b> 11mm x 25.9mm 78% Open Area 4.2kg/m<sup>2</sup></p> </td> <td> <p><b>Rhombic 7</b> 12.6mm x 30.5mm 84% Open Area 4.2kg/m<sup>2</sup></p> </td> </tr> </table>	<p><b>Hexagon 1</b> 7.2mm x 26.4mm 74% Open Area 5.0kg/m<sup>2</sup></p>	<p><b>Hexagon 3</b> 3.75mm x 26.4mm 80% Open Area 7.1kg/m<sup>2</sup></p>	<p><b>Rhombic 4</b> 11mm x 25.9mm 78% Open Area 4.2kg/m<sup>2</sup></p>	<p><b>Rhombic 7</b> 12.6mm x 30.5mm 84% Open Area 4.2kg/m<sup>2</sup></p>
<p><b>Hexagon 1</b> 7.2mm x 26.4mm 74% Open Area 5.0kg/m<sup>2</sup></p>	<p><b>Hexagon 3</b> 3.75mm x 26.4mm 80% Open Area 7.1kg/m<sup>2</sup></p>	<p><b>Rhombic 4</b> 11mm x 25.9mm 78% Open Area 4.2kg/m<sup>2</sup></p>	<p><b>Rhombic 7</b> 12.6mm x 30.5mm 84% Open Area 4.2kg/m<sup>2</sup></p>		
<b>Patterns</b>	<b>Welded and Woven Mesh</b>				
<b>Weight</b>	<table border="0"> <tr> <td> <p><b>Welded – Small Square</b> 25.6mm 78% Open Area 4.3kg/m<sup>2</sup></p> </td> <td> <p><b>Welded – Big Square</b> 59.4mm 88% Open Area 2.3kg/m<sup>2</sup></p> </td> <td> <p><b>Woven – Square Wire</b> 19.5mm / 6.4mm 53% Open Area 4.0kg/m<sup>2</sup></p> </td> <td> <p><b>Woven – Linear Wire</b> 10mm / 19.5mm 62% Open Area 6.5kg/m<sup>2</sup></p> </td> </tr> </table>	<p><b>Welded – Small Square</b> 25.6mm 78% Open Area 4.3kg/m<sup>2</sup></p>	<p><b>Welded – Big Square</b> 59.4mm 88% Open Area 2.3kg/m<sup>2</sup></p>	<p><b>Woven – Square Wire</b> 19.5mm / 6.4mm 53% Open Area 4.0kg/m<sup>2</sup></p>	<p><b>Woven – Linear Wire</b> 10mm / 19.5mm 62% Open Area 6.5kg/m<sup>2</sup></p>
<p><b>Welded – Small Square</b> 25.6mm 78% Open Area 4.3kg/m<sup>2</sup></p>	<p><b>Welded – Big Square</b> 59.4mm 88% Open Area 2.3kg/m<sup>2</sup></p>	<p><b>Woven – Square Wire</b> 19.5mm / 6.4mm 53% Open Area 4.0kg/m<sup>2</sup></p>	<p><b>Woven – Linear Wire</b> 10mm / 19.5mm 62% Open Area 6.5kg/m<sup>2</sup></p>		
<b>Dimensions (mm)</b>	600 x 600 1200 x 600				
<b>Suspension System</b>	Standard Peakform Prelude 24mm				
<b>Colour</b>	Polyester Powder Coated - Global White / Black / Silver Grey				
<b>Sound absorption</b>	N.A. *Optional Range of infill available up to NRC0.90				
<b>Fire reaction</b>	CLASS 0/1 based on BS 476 Part 6 & 7				
<b>Handling</b>	100% upward demountable without tooling.				

All sizes are nominal. Product availability may vary.

## Contact

For further details, please contact your local representative or email [asia.support@knaufarmstrong.com](mailto:asia.support@knaufarmstrong.com)