



ARMSTRONG METALWORKS™ VECTOR

- Monolithic concealed ceiling visual with a sleek 6.0mm reveal between panel
- Cost effective installation on standard 24mm Peakform Tee grid
- Simple accessibility: Downward demountable with minimal plenum clearance
- High sound absorption for reduced reverberation and quieter spaces
- Factory fitted security spring to secure panel on removal
- Used in a variety of ceiling areas: from small service rooms to large commercial office buildings and major transportation terminals

Panel Options	Vector: Modular Concealed System with 6.00mm Reveal			
Edge details				
Material	Galvanized Steel			
Patterns * Perforated panels feature an unperforated border and include acoustical fleece.	<p>Non Perforated (M1)</p>	<p>Micro Perforated (M2) 1.5mm Ø 19% Open Area</p>	<p>Micro Perforated (M9) 1.5mm Ø 9.5% Open Area</p>	<p>Standard Perforated (M10) 2.5mm Ø 16% Open Area</p>
Dimensions (mm)	600 x 600 1200 x 600 (Other sizes available on request)			
Suspension System	Peakform Prelude XL43 Suspension System			
Weight	≈4.6 kg/m ²			
Colour	Polyester Powder Coated – Global White Wood Effects Available by Request			
Sound absorption	NRC 0.70 (M2) / NRC 0.75 (M9) / NRC 0.80 (M10) - Perforated Option with fleece, without additional infill. Contact your local sales representative for test data.			
Sound attenuation	Approximately 18 dB (without additional infill). Optional: High Attenuation Performance Up to 38dB (NRC 0.60) with additional mineral infill.			
Fire reaction	CLASS 0/1 based on BS 476 Part 6 & 7			
Handling	100% downward demountable without tooling. All Vector Panel are factory fitted with security spring			
Durability				
Cleanability				

All sizes are nominal. Product availability may vary.

Contact

For further details, please contact your local representative or email asia.support@knaufarmstrong.com